

# LamRite Roll Films

## 1.5 Mil Film For Heated Roller Laminators

25" X 500' ON 1" CORE

**SPECIFICATION:**

ITEM	UNIT	STANDARD	TEST METHOD
Total thickness	mil	1.5 ±5%	
PET	mil	0.5 ±5%	
LDPE	mil	1 ±5%	
Width	inch	25 ± 0.04	
Length	feet	500 -0/+3	
O.D.	inch	3.6 ± 0.1	
Paper core	inch	1 -0/+0.01	
Net Weight	kg / lbs.	3.45 / 7.61	
Tensile strength	kg/mm2	MD	ASTM D882
		TD	
Elongation	%	MD	ASTM D882
		TD	
Melting Point	Fahrenheit / Celsius	226 ±37.4 / 108 ±3	ASTM D2117
Softing Point	Fahrenheit / Celsius	185 ±37.4 / 85 ±3	ASTM D1525

27" X 500' ON 1" CORE

**SPECIFICATION:**

ITEM	UNIT	STANDARD	TEST METHOD
Total thickness	mil	1.5 ±5%	
PET	mil	0.5 ±5%	
LDPE	mil	1 ±5%	
Width	inch	27 ± 0.04	
Length	feet	500 -0/+3	
O.D.	inch	3.6 ± 0.1	
Paper core	inch	1 -0/+0.01	
Net Weight	kg / lbs.	3.80 / 8.38	
Tensile strength	kg/mm2	MD	ASTM D882
		TD	
Elongation	%	MD	ASTM D882
		TD	
Melting Point	Fahrenheit / Celsius	226 ±37.4 / 108 ±3	ASTM D2117
Softing Point	Fahrenheit / Celsius	185 ±37.4 / 85 ±3	ASTM D1525