

The preferred method of shrink-wrapping around the world is now available in North America.

Our one-step systems eliminate the need for manual "L" bar sealers and tunnels by performing both operations under one hood.



ONE STEP SHRINK WRAP

Specs	Baby 1217	1217 ST	4255 MAG	4255 Plus EV
Power Supply	110v - 20 amp	110v - 20 amp	220v- 20amp	220v- 20amp
Sealing area	12" x 17"	12.5" x 17"	16.5" x 21.5"	16.5" x 21.5"
Max. product height	6"	6"	8"	8"
Sealing type	Wire	Micro Knife	Micro knife	Micro knife
Magnetic hold down	NO	YES	YES	YES
Pack speed	4-6 p/m	4-6 p/m	6-8 p/m	10-14 p/m
Max centerfold film	14"	16"	22"	22"
Overall dimensions	22" x 25"	26" x 33.5"	53" x 41"	53" x 41"
Shipping wt.	200 lbs.	220 lbs.	320 lbs.	360 lbs.



ONE STEP SHRINK WRAP

Specs	6084	75125	85150
Power Supply	110v - 20 amp	110v - 20 amp	220v- 20amp
Sealing area	23" x 33"	29" x 49"	33" x 59"
Max. product height	10"	10"	10"
Sealing type	Micro knife	Micro knife	Micro knife
Magnetic hold down	YES	YES	YES
Pack speed	4-6 p/m	4-6 p/m	4-6 p/m
Max centerfold film	32"	42"	50"
Overall dimensions	37.5" X 73"	51" X 106"	61" X 100"
Shipping wt.	550 lbs.	700 lbs.	850 lbs.