

ALM 3222 Automatic Laminator



Laminates paper up to 130 lb cover stock

Virtually Unattended Operation

SPECIFICATIONS:

Model No.:	ALM 3222
Laminating Speed:	20" - 68"/min.
Temperature Range:	170-270°F
Ultra Fast Warm-Up Time:	Approx. 5 minutes
Thickness of Substrates:	20 lb bond - 130lb cover
Paper Feeding Capacity:	200 sheets, Adjustable Paper Guide
Applicable Paper Sizes:	
	Letter Paper Size 8.5" x 11"
	Paper Size 13" x 19"
	Paper Size 12" x 18"
	Tabloid Paper Size 11" x 17"
Trimming Methods:	(2 modes) Flush cut applications or sealed edges seal for all 4 sides of the print
Operation Panel:	LCD display for start, stop, temperature, speed and trim settings, leading and trailing edge side cuts are adjustable
Other Features:	Laminated sheet counter; Film tension control, Roller gap lever, Paper thickness adjustment lever, Automatic stop at end of film, Power saving mode, Emergency stop function
Power Consumption:	1200W
Power Supply:	120 VAC, 60Hz, 10A
Net Weight:	Laminator: 130 lbs. Stand: 48.5 lbs.
Included Accessories:	Stand with film waste box, Printed operations manual

- 120 Volt, 10 amp service with economy mode
- Ultra quick warm up of approximately 5 minutes
- Sheet sizes: 13"x19", 12"x18", 11"x17", & 8.5"x11"
- Automatic single or double sided lamination
- Adjustable for automatically flush cut or sealed edge trim options; micro adjustable for precise flush cut or custom encapsulation
- 1 year parts and 90 day labor warranty

ALM Exclusive ASAP Roll Film

- Perfect for Digital Print technology
- Anti-static properties

Gloss & matte versions available in the following:

- 1.5mil, 12.6" x 984 ft
- 3.0mil, 12.6" x 492 ft
- 5.0mil, 12.6" x 328 ft
- 10.0mil, 12.6" x 165 ft (Gloss Only)
- 1.2mil, 12.6" x 984 ft, Nylon (Gloss & Matte Versions)